

■ VETO Recessed LED Downlight



Application

Office, Building, Hospital, Retail, Museum

Characteristic

Light source	: LED
Power correction factor	: > 0.5 / > 0.9*
Compliance	: MS IEC 60598-1
	: MS IEC 60598-2-2
Ingress Protection (IP)	: IP20
Colour rendering (CRI)	: ≥ 80
Colour temperature (CCT)	: 3000K ~ 6000K (Selectable)
<i>Other CCT & CRI available upon request</i>	
Weight	: < 0.5 kg
Beam Angle	: 120°
Wattage	: 5W ~ 24W
Nominal efficacy	: 85 lm/W
Useful life	: 25,000 hours ~ Base on the light source
Operating temperature range (Ta)	: -20°C + 40°C
Driver	: Driver on board
Main voltage	: 220 ~ 240V / 50 ~ 60Hz

Features

- Easy recess installation.
- Ideal for commercial usage with minimum maintenance
- 50% more efficient than CFL Downlights.
- Selectable CCT.
- Anti glare frosted diffuser.
- Motion Sensor / Microwave*.

* Item upon request

Product Speciality



Easy Installation

Ordering Code Dimension : VETO Recessed

Code	Wattage	Nominal Flux	Power Factor	Cut Out (mm)	Size (mm)	Weight(kg)
VRR005CS	5W	425	0.5	Φ75-90mm	Φ95xH26mm	0.04
VRR009CS	9W	765	0.5	Φ90 -110mm	Φ120xH26mm	0.07
VRR012CS	12W	1020	0.5	Φ120 -210mm	Φ145xH26mm	0.09
VRR018CS	18W	1530	0.5	Φ140 - 160mm	Φ170xH26mm	0.12
VRR024CS	24W	2040	0.5	Φ190 - 210mm	Φ225xH26mm	0.19
VRS005CS	5W	425	0.5	75 - 90 x 75 - 90mm	95x95xH26mm	0.04
VRS009CS	9W	765	0.5	90 -110 x 90 -110mm	120x120xH26mm	0.08
VRS012CS	12W	1020	0.5	120 -135 x 120 -135mm	145x145xH26mm	0.10
VRS018CS	18W	1530	0.5	140 -160 x 140 -160mm	170x170xH26mm	0.16
VRS024CS	24W	2040	0.5	190 -210 x 190 -210mm	225x225xH26mm	0.29

* The above ordering code is base on CCT SELECTABLE

Ordering Code Dimension : VETO Recessed Professional

Code	Wattage	Nominal Flux	Power Factor	Cut Out (mm)	Size (mm)	Weight(kg)
VRR00560-P	5W	425	0.9	Φ75-90mm	Φ95xH26mm	0.04
VRR00960-P	9W	765	0.9	Φ90 -110mm	Φ120xH26mm	0.07
VRR01260-P	12W	1020	0.9	Φ120 -210mm	Φ145xH26mm	0.09
VRR01860-P	18W	1530	0.9	Φ140 - 160mm	Φ170xH26mm	0.12
VRR02460-P	24W	2040	0.9	Φ190 - 210mm	Φ225xH26mm	0.19
VRS00560-P	5W	425	0.9	75 - 90 x 75 - 90mm	95x95xH26mm	0.04
VRS00960-P	9W	765	0.9	90 -110 x 90 -110mm	120x120xH26mm	0.08
VRS01260-P	12W	1020	0.9	120 -135 x 120 -135mm	145x145xH26mm	0.10
VRS01860-P	18W	1530	0.9	140 -160 x 140 -160mm	170x170xH26mm	0.16
VRS02460-P	24W	2040	0.9	190 -210 x 190 -210mm	225x225xH26mm	0.29

* The above ordering code is base on CCT~6000K

Photometry